



Control panel



1500 rpm Kubota engine



Fuel inlet and outlet



We offer now what others will do tomorrow.



## Genset s.p.a.

Via Stazione 5 - 27030 Villanova d'Ardenghi (PV) - Italy Phone:+39-0382-5091

commerciale@genset.it www.genset.it



## MG 9.5 DK / TECHNICAL DATA

VEHICULAR GENERATOR
OUTPUT POWER 10 kVA SINGLE-PHASE
KUBOTA DIESEL ENGINE 1500 RPM
SUPER-SILENCED VERSION

#### Standard Features

- Remote control panel with: multifunction display showing single-phase generator voltage, battery voltage, frequency, hour meter, rpm
- Built-in control panel
- Start / Stop button
- Connection cable to remote panel
- · Safety shutdown in case of: low oil level, high water temperature
- Engine failure warning lights
- Operation lamp
- Hourmeter
- Circuit breaker for the generator protection
- General shutdown switch
- Faults memory
- External muffler

# Options available as factory options

- 20 lt plastic fuel tank with brackets
- 20 It steel fuel tank with brackets
- Fuel reserve indicator kit
- Fuel filler with key lock cap
- I mt fuel pipe for connection tank-fuel filler
- Fuel pipe I/O to the automatic tank
- CBU remote control panel with 20 mt cable

#### Noise level

• Lwa 83 (58 dB a 7 mt)

#### AC generator - 50Hz

- Type: synchronous
- Single-phase power (max.): 10 kVA 230V
- Power Factor: cos φ 0,8

### Diesel Engine 1500 rpm

- Type: Kubota D1105 3 cyl. 12,7 hp (9,5 kWm) 1123 cm<sup>3</sup>
- Cooling system: water
- · Starting system: electric
- Fuel consumption @ 75%: 2 lt/h

#### Other features

- Insulation Class: H
- Ambient temperature: 40 °C (\*)
- Altitude: 1000 mt (\*)
- Mechanical Protection: IP 23
- Dimensions (L  $\times$  W  $\times$  H): 1070  $\times$  560  $\times$  660 mm
- Dry weight: 320 kg