MG 6/5 S-Y





Control panel



Central lifting eye



10,5 It Fuel Tank



We offer now what others will do tomorrow.



Genset s.p.a.

Via Stazione 5 - 27030 Villanova d'Ardenghi (PV) - Italy Phone:+39-0382-509 I

commerciale@genset.it www.genset.it

GenSet

Next Gen technology
for top business.

MG 6/5 S-Y / TECHNICAL DATA

SILENCED POWER GENERATOR
OUTPUT POWER 6,3 KVA THREE-PHASE AND 4,4 KVA SINGLE-PHASE
3000 RPM DIESEL ENGINE
10.5 LT FUEL TANK

Standard Features

- Voltmeter
- Hourmeter
- Earth leakage circuit breaker
- Emergency stop button
- Starter battery
- I x I6 A, 400 V 50 Hz EEC three-phase socket
- 1 x 16A, 230V 50 Hz EEC single-phase socket
- Power output protection
- Fitted for AMF/ATS or Remote control operation
- · Central lifting eye

Options available as factory options

- · Versions with different voltages
- 60Hz version
- Oversized fuel tank
- Automatic voltage regulator (AVR)

Accessories on request

- AMF/ATS panel for auto start operation
- Trolley: two-wheels and handles
- Remote START/STOP kit

Noise level

• Lwa 97 (72 dB a 7 mt)

AC generator - 50Hz

- Type: synchronous
- Three-phase power (max.): 6,3 kVA 400 V
- Single-phase power (max.): 4,4 kVA 230 V
- Power Factor: cos φ 0,8

Diesel Engine 3000 rpm

- Type: Yanmar L100V 1 cyl. 8,8 hp (6,5 kWm) 435 cm³
- · Cooling system: air
- Starting system: electric
- Fuel tank capacity: 10,5 lt
- Fuel consumption @ 75%: I,5 lt/h

Other features

- Insulation Class: H
- Ambient temperature: 40 °C (*)
- Altitude: 1000 mt (*)
- Mechanical Protection: IP 23
- Dimensions (L \times W \times H): 815 \times 560 \times 730 mm
- Dry weight: 150 kg