

MG 5000 I-HE 25 It



Fuel Tank of 25 It



Front Panel



Handles



Stage V

We offer now what others will do tomorrow.



GenSet s.p.a.

Via Stazione 5 - 27030
Villanova d'Ardenghi (PV) - Italy
Phone: +39-0382-5091

commerciale@genset.it
www.genset.it

GenSet
Next Gen technology
for top business.

PORTABLE SINGLE-PHASE POWER GENERATOR

OUTPUT POWER 5kVA

PETROL ENGINE 3000 RPM

FUEL TANK 25 lt

Standard Features	<ul style="list-style-type: none"> • Low oil level shutdown device • 2 x 230 V - 50 Hz single-phase Schuko socket protected by circuit breaker • 12Vdc battery charger outlet protected by fuse
Options available as factory options	<ul style="list-style-type: none"> • Versions with different voltages • 60Hz version • Automatic voltage regulator (AVR)
Accessories on request	<ul style="list-style-type: none"> • Trolley: two-wheels and handles
Noise level	<ul style="list-style-type: none"> • Lwa 96 (71 dB a 7 mt)
AC generator - 50Hz	<ul style="list-style-type: none"> • Type: synchronous • Single-phase max. power: 5 kVA - 230 V • Battery charger power: 120 W - 12 V - 10 A - DC • Power Factor: $\cos \phi$ 0,8
Petrol Engine 3000 rpm	<ul style="list-style-type: none"> • Type: Honda GX 270 OHV - 1 cyl. 7,8 HP (5,8 kWm) - 270 cm³ • Cooling system: air • Starting system: recoil • Fuel tank capacity: 25 lt • Fuel consumption @ 75%: 2,2 lt/h
Other features	<ul style="list-style-type: none"> • Insulation Class: H • Ambient temperature: 40 °C (*) • Altitude: 1000 mt (*) • Mechanical Protection: IP 23 • Dimensions (L x W x H): 770 x 480 x 625 mm • Dry weight: 71 kg