

MG 6000 BS/HA AVR



Control Panel



Movable Base



Concealable Handles



Stage V

We offer now what others will do tomorrow.



Genset s.p.a.

Via Stazione 5 - 27030
Villanova d'Ardenghi (PV) - Italy
Phone: +39-0382-5091

commerciale@genset.it
www.genset.it

 **GenSet**
Next Gen technology
for top business.

SUPER SILENCED POWER GENERATOR
OUTPUT POWER 5 KVA SINGLE-PHASE
PETROL ENGINE 3000 RPM
10,5 LT FUEL TANK

Standard Features	<ul style="list-style-type: none"> • Low oil level shutdown device • 12V battery • 1 x 16 A, 230V - 50 Hz single-phase EEC socket • Protections for power outputs • Earth leakage circuit breaker (ELCB) • Voltmeter • Hourmeter • Fixed wheels and concealable handles for moving • Fitted for AMF-ATS or Remote control operation • Choke switch • Automatic voltage regulator (AVR)
Options available as factory options	<ul style="list-style-type: none"> • Versions with different voltages • 60Hz version
Accessories on request	<ul style="list-style-type: none"> • AMF/ATS panel for auto start operation • Remote control
Noise level	<ul style="list-style-type: none"> • Lwa 86 (61 dB a 7 m)
AC generator - 50Hz	<ul style="list-style-type: none"> • Type: synchronous • Single-phase power (standby): 5 kVA - 230V • Power Factor: $\cos \phi$ 0,8
Petrol Engine 3000 rpm	<ul style="list-style-type: none"> • Type: Honda GX270 - 1 cyl. - STAGE V - 8,2 hp (6 kWm) - 270 cm³ • Cooling system: air • Starting system: electric (12Vdc) • Fuel tank capacity: 10,5 lt • Fuel consumption @ 75%: 2,2 lt/h
Other features	<ul style="list-style-type: none"> • Insulation Class: H • Ambient temperature: 40 °C (*) • Altitude: 1000 mt (*) • Mechanical Protection: IP 23 • Dimensions (L x W x H): 1059 x 670 x 740 mm • Dry weight: 125 kg

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.
In line with our continued development, innovation and voice of customer program, we reserve the right to change data without notice.