# MG 8000 BS/HA AVR





Control Panel



Movable Base



Concealable Handles



We offer now what others will do tomorrow.



## Genset s.p.a.

Via Stazione 5 - 27030 Villanova d'Ardenghi (PV) - Italy Phone:+39-0382-5091

commerciale@genset.it www.genset.it



# MG 8000 BS/HA AVR / TECHNICAL DATA

SUPER SILENCED POWER GENERATOR **OUTPUT POWER 7 KVA SINGLE-PHASE** PETROL ENGINE 3000 RPM **FUEL TANK 10,5 LT** 

### Standard Features

- · Low oil level shutdown device
- I2V battery
- I x 16 A, 230 V 50 Hz single-phase EEC socket
- I x 32 A, 230 V 50 Hz single-phase EEC socket
- Protections for power outputs
- Earth leakage circuit breaker (ELCB)
- Voltmeter
- Hourmeter
- Fixed wheels and concealable handles for moving
- Fitted for AMF-ATS or Remote control operation
- Choke switch
- Automatic voltage regulator (AVR)

#### **Options** available as factory options

- Versions with different voltages
- 60Hz version

## Accessories on request

- AMF/ATS panel for auto start operation
- Remote control

#### Noise level

• Lwa 86 (61 dB at 7 mt)

## AC generator - 50Hz

- Type: synchronous
- Single-phase power (standby): 7 kVA 230 V
- Power Factor: cos φ 0,8

## **Petrol Engine** 3000 rpm

- Type: Honda GX390 1 cyl. 390 cm<sup>3</sup>
- Max power: II hp (8,2 kWm)
- Starting system: electric (12Vdc)
- Cooling system: air
- Fuel consumption @ 75%: 3,3 lt/h

#### Other features

- Insulation Class: H
- Ambient temperature: 40 °C (\*)
- Altitude: 1000 m (\*)
- Mechanical Protection: IP 23
- Fuel tank capacity: 10,5 lt Dimensions (L  $\times$  W  $\times$  H): 1059  $\times$  670  $\times$  740 mm
- Dry weight: 138 kg