

# MG 1200 I IHPAA



Front Panel



29 It Fuel tank



Lifting eye



Stage V

We offer now what others will do tomorrow.



**GenSet s.p.a.**

Via Stazione 5 - 27030  
Villanova d'Ardenghi (PV) - Italy  
Phone: +39-0382-5091

commerciale@genset.it  
www.genset.it

 **GenSet**  
Next Gen technology  
for top business.

**POWER GENERATOR**  
**OUTPUT POWER 11 kVA SINGLE-PHASE**  
**PETROL ENGINE 3000 RPM**  
**29 LT FUEL TANK**

<p><b>Standard Features</b></p>	<ul style="list-style-type: none"> <li>• Low oil level shutdown device</li> <li>• 12V battery</li> <li>• 1 x 16 A, 230V - 50 Hz single-phase EEC socket</li> <li>• 1 x 32 A, 230V - 50 Hz single-phase EEC socket</li> <li>• Protections for power outputs</li> <li>• Earth leakage circuit breaker</li> <li>• Voltmeter</li> <li>• Hourmeter</li> <li>• Automatic voltage regulator (AVR)</li> <li>• Fitted for AMF-ATS or Remote control operation</li> <li>• Central lifting eye</li> </ul>
<p><b>Options</b> available as factory options</p>	<ul style="list-style-type: none"> <li>• Versions with different voltages</li> <li>• 60Hz version</li> </ul>
<p><b>Accessories</b> on request</p>	<ul style="list-style-type: none"> <li>• AMF/ATS panel for auto start operation</li> <li>• Remote control</li> <li>• Trolley: two-wheels and handles</li> </ul>
<p><b>Noise level</b></p>	<ul style="list-style-type: none"> <li>• Lwa 96 (71 dB a 7 mt)</li> </ul>
<p><b>AC generator - 50Hz</b></p>	<ul style="list-style-type: none"> <li>• Type: synchronous</li> <li>• Single-phase power (standby): 11 kVA - 230V</li> <li>• Single-phase power (prime): 10 kVA - 230V</li> <li>• Power Factor: <math>\cos \phi</math> 0,8</li> </ul>
<p><b>Petrol Engine</b> 3000 rpm</p>	<ul style="list-style-type: none"> <li>• Type: Honda GX630 - 2 cyl. - 688 cm<sup>3</sup></li> <li>• Max power: 19,8 hp (14,6 kWm)</li> <li>• Starting system: electric (12Vdc)</li> <li>• Cooling system: air</li> <li>• Fuel consumption @ 75%: 5,5 lt/h</li> </ul>
<p><b>Other features</b></p>	<ul style="list-style-type: none"> <li>• Insulation Class: H</li> <li>• Ambient temperature: 40 °C (*)</li> <li>• Altitude: 1000 m (*)</li> <li>• Mechanical Protection: IP 23</li> <li>• Fuel tank capacity: 29 lt</li> <li>• Dimensions (L x W x H): 914 x 566 x 847 mm</li> <li>• Dry weight: 202 kg</li> </ul>

(\*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.  
In line with our continued development, innovation and voice of customer program, we reserve the right to change data without notice.